

Model	SUNON PRO 3.5K	SUNON PRO 5.5K
The rated power	3500VA/3500W	5500VA/5500W
INPUT		
Voltage	230VAC	
Selectable Voltage Range	170-280VAC (UPS),90-280VAC (Appliances)	
Frequency Range	50Hz/60Hz (Auto sensing)	
OUTPUT		
AC Voltage Regulation (Batt. Model)	230VAC ± 5%	
Surge Power	7000VA	11000VA
Power factor	1,0	1,0
Efficiency(Peak)	> 90%	
Transfer Time	10ms (UPS), 20ms (Appliances)	
Wave form	Pure sine wave	
No load current	1.0A	1.1A
BATTERY		
Battery voltage	24VDC	48VDC
Low battery alarming voltage	22.0VDC	44.0VDC
Low battery cut off protection voltage	21VDC	42VDC
Low battery recovery voltage	23.0VDC	46.0VDC
Floating Charge Voltage	27VDC	54VDC
Overcharge Protection	32VDC	64VDC
MPPT SOLAR CHARGER & AC CHARGER		
Maximum PV Array Power	5000W	5000W
MPPT Range Operation Vol	120-450VDC	120-450VDC
Maximum PV Array Open Circuit Vol.	500VDC	500VDC
Number of MPPT trackers / Max output current	100A	100A
Maximum AC Charge Current	60A	60A
Maximum Charge Current	100A	100A
Maximum Efficiency	98%	
BEST PANEL CONFIGUTATION		
Maximum PV Array Power	5000W	6000W
Best Panel configuration	300Wp*9pcs*36V(2700Wp)*2Parallel	330Wp*9pcs*36V(2700Wp)*2Parallel
PHYSICAL		
Products Dimension, D*W*H(mm)	481mm*313mm*117mm	481mm*313mm*117mm
Packing size, D*W*H(mm)	543mm*394mm*204mm	543mm*394mm*204mm
Net Weight (kgs)	9.8Kg	10.5Kg
G.W. kg	11.2Kg	11.8Kg
OPERATING ENVIRONMENT		
Humidity	5% to 95% Relative Humidity (Non-condensing)	
Operation Temperature	0℃-50℃	
PRODUCT PICTURES		



Product specifications are subject to change without further notice