




fangpusun solar charge controller mppt 150/45,150/60,150/70

Ultra-fast Maximum Power Point Tracking (MPPT)

Especially in case of a clouded sky, when light intensity is changing continuously, an ultra-fast MPPTcontroller will improve energy harvest by up to 30% compared to PWM charge controllers and by up to 10% compared to slower MPPT controllers.

Advanced Maximum Power Point Detection in case of partial shading conditions

If partial shading occurs, two or more maximum power points may be present on the power-voltage curve. Conventional MPPT's tend to lock to a local MPP, which may not be the optimum MPP. The innovative Fangpusun algorithm will always maximize energy harvest by locking to the optimum MPP.

Outstanding conversion efficiency

No cooling fan. Maximum efficiency exceeds 98%.

Flexible charge algorithm

Fully programmable charge algorithm (see the software page on our website), and eight preprogrammed algorithms, selectable with a rotary switch (see manual for details).

Extensive electronic protection

- Over-temperature protection and power derating when temperature is high.
- PV short circuit and PV reverse polarity protection.
- PV reverse current protection.

Internal temperature sensor

- Compensates absorption and float charge voltage for temperature.


Real-time data display options

- Apple and Android smartphones, tablets and other devices: see the VE.Direct to Bluetooth Smart dongle
- ColorControl panel

Certificates

- Compliant with European Standards (CE)
- RoHS compliant
- SGS
- ISO 9001
- Made in China

Fangpusun Solar Charge Controller	MPPT150/45	MPPT150/60	MPPT150/70
Battery voltage	12 / 24 /48 V Auto Select (software tool needed to select 36 V)		
Rated charge current	45 A	60 A	70 A
Maximum PV power, 12V 1a,b)	650 W	860W	1000W
Maximum PV power, 24V 1a,b)	1300W	1720W	2000W
Maximum PV power, 48V 1a,b)	2600W	3440W	4000W
Maximum PV open circuit voltage	150V absolute maximum coldest conditions , 145V start-up and operating maximum		
Maximum efficiency	98 %		
Self-consumption	10 mA		
Charge voltage 'absorption	Default setting: 14,4 / 28,8 / 43,2 / 57,6 V (adjustable)		
Charge voltage 'float'	Default setting: 13,8 / 27,6 / 41,4 / 55,2 V (adjustable)		
Charge algorithm	multi-stage adaptive		
Temperature compensation	-16 mV / °C resp. -32 mV / °C		
Protection	Battery reverse polarity (fuse, not user accessible) PV reverse polarity / Output short circuit / Over temperature		
Operating temperature	-30 to +60°C (full rated output up to 40°C)		
Humidity	95 %, non-condensing		
Data communication port and remote	VE.Direct (see the data communication white paper on our website)		
Parallel operation	Yes (not synchronized)		
ENCLOSURE			
Colour	Blue (RAL 5012)		
PV terminals 2)	35 mm² / AWG2 (Tr models), or Dual MC4 connectors (MC4 models)		
Battery terminals	35 mm² / AWG2		
Protection category	IP43 (electronic components), IP22 (connection area)		
Weight	3 kg		
Dimensions (h x w x d)	Tr models: 200 x 250 x 95 mm,MC4 models: 230 x 250 x 95 mm		
STANDARDS			
Safety	IEC 62109-1-2010		
1a) If more PV power is connected, the controller will limit input power to the stated maximum. 1b) PV voltage must exceed Vbat + 5V for the controller to start.Thereafter minimum PV voltage is Vbat + 1V 2) MC4 models: several splitter pairs will be needed to parallel the strings of solar panels			



Maximum Power Point Tracking

Upper curve:
Output current (I) of a solar panel as function of output voltage (V).
The maximum power point (MPP) is the point Pmax along the curve where the product I x V reaches its peak.

Lower curve:
Output power P = I x V as function of output voltage.
When using a PWM (not MPPT) controller the output voltage of the solar panel will be nearly equal to the voltage of the battery, and will be lower than Vmp.